



CREEPAGE DISTANCE : 75mm

| ITEM | QTY | DESCRIPTION | DIMENSION | MAT'L | ITEM CODE | REMARKS |
|------|-----|---------------------|-------------|-------------------|-----------|---------|
| 14 | 2 | Bolt M12x65 | - | Stainless Steel | | |
| 13 | 2 | Plain Washer M12 | - | Stainless Steel | | |
| 12 | 1 | Connection Flag | 210x120x15 | Brass | | |
| 11 | 1 | Brass Half Nut M48 | - | Brass | | |
| 10 | 1 | "E" Washer | Ø85xØ50x24 | Brass | | |
| 9 | 1 | "J" Gasket 65x48x18 | - | NBR | | |
| 8 | 1 | "G" Washer | Ø90xØ50x8 | Brass | | |
| 7 | 1 | "M" Gasket 90x50x4 | - | Cork Rubber | | |
| 6 | 1 | Top Porcelain | Ø125xØ50x90 | Ceramic Porcelain | | |
| 5 | 1 | "N" Gasket 125x90x6 | - | Cork Rubber | | |
| 4 | 1 | "X" Gasket 125x90x3 | - | Pressboard | | |
| 3 | 1 | Bottom Insulator | 123x123x38 | Nylon PA-66 | | |
| 2 | 1 | Stem Bottom Part | 110x110x30 | Brass | | |
| 1 | 1 | Stem | M48x276 | Copper | | |

| ITEM | QTY | DESCRIPTION | DIMENSION | MAT'L | ITEM CODE | REMARKS |
|---|----------|-------------|-----------|----------------------------|--|-------------|
| 00 | 14/04/23 | RV | MA | MA | Original | |
| Rev | Date | Drw | Chk | App | Description | |
| General Tolerance Machining : ISO 2768 - Coarse | | | | Surface Texture : ISO 1302 | All dimension in millimetres unless otherwise stated | |
| IF IN DOUBT - PLEASE ASK ! | | | | | | |
| | | | | Title | | |
| | | | | LV Bushing 1kV/3150A EN | | |
| | | | | Description | | Scale |
| | | | | EN 1/3150A | | 1 : 2 |
| Metson Power Çamlıca Mah. Anadolu Bulv. Timco İşyerleri B Blok No:6 06200 Yenimahalle, Ankara TURKEY | | | | Drawing No. | Sheet No. | Total Sheet |
| | | | | ID_A0106100 | 1 | 1 |
| | | | | | | A3 |

This document is the exclusive property of METSON POWER. And shall not be used, copied or communicated to third parties without its prior authorisation.